



TECHNICAL DATA SHEET
MASKING FILM

Gerko HDPE masking film is perfect for quick and efficient covering of a vehicle and protects it against overspray, dirt and dust.

PROPERTIES

- Translucent HDPE masking film to protect from overspray, dirt and dust
- Corona treated with Gerko logo on the paintable side
- Easy to use by one man
- Strong and elastic performance
- Easy to cut
- Static properties, clings to the object surface
- Per roll in a carton box
- Can be used with infrared drying
- Thickness: 10 µm

PHYSICAL PROPERTIES

Code	Description	Dimensions	Colour	Pieces per box	Pieces per pallet
PM4015	Masking Film 4m x 150m	4m x 150m	Transparent	1	112
PM40	Masking Film 4m x 300m	4m x 300m	Transparent	1	84
PM48	Masking Film 4,8m x 300m	4,8m x 300m	Transparent	1	60
PM50	Masking Film 5m x 120m	5m x 120m	Transparent	1	135
PM60	Masking Film 6m x 100m	6m x 100m	Transparent	1	112

PRODUCT INFORMATION

Form	Material	Roll width	Temperature resistance	Water soluble
Film on a roll	HDPE	95 cm	120°C	No



TECHNICAL DATA SHEET
MASKING FILM

TECHNICAL PROPERTIES



Paint adhesive



High static power



High tensile strength



IR drying by max 120°C

STORAGE

+ 20°C/± 10°C, in an enclosed space with a relative humidity of 30-90% without exposure to UV

SHELF LIFE

12 months from delivery date