



TECHNICAL DATA SHEET

SUPERIOR MASKING FILM

The Gerko blue transparent masking film has a special layer on the inside that absorbs any moisture residues on the car, so it can be applied to damp surfaces and prevents 'false spots'. This masking film is made extra thick, making it even stronger.

PROPERTIES

- Corona treated for optimal adhesion of paint and overspray
- Special addition that ensures moisture absorption, in addition to the breathable functionality
- Foil thickness: 15 µm
- Easy to apply by one person
- Strong and elastic performance
- Easy to cut
- Statically charged, causing the film to be attracted to the surface
- Packed per roll in a carton box
- Can be used with infrared drying
- Temperature resistant up to 120°C
- Gerko logo on spray side

PHYSICAL PROPERTIES

Code	Description	Dimensions	Colour	Pieces per box	Pieces per pallet
SPM40	Superior Masking Film Moisture absorbent 4m x 150m 15 µm	4m x 150m	Blue	1	96
SPM50	Superior Masking Film Moisture absorbent 5m x 120m 15 µm	5m x 120m	Blue	1	96

PRODUCT INFORMATION

Form	Material	Roll width	Temperature resistance	Water soluble
Film on a roll	HDPE	95 cm	120°C	No



TECHNICAL DATA SHEET

SUPERIOR MASKING FILM

TECHNICAL PROPERTIES



Paint adhesive



High static power



High tensile strength



IR drying by max 120°C



Breathable



Moisture absorbent

STORAGE

+ 20°C/± 10°C, in an enclosed space with a relative humidity of 30-90% without exposure to UV

SHELF LIFE

12 months from delivery date