in fo@gerkoproducts.com+32 (0)3 312 21 30 WWW.GERKOPRODUCTS.COM

TECHNICAL DATA SHEET **DUCT TAPE**

Gerko duct tape has been specially developed to protect vehicle parts during sanding and blasting work. Also useful when transporting a damaged vehicle.

PROPERTIES

- Excellent adhesion properties at low & high temperatures
- Good performance on rough surface
- Excellent tearing & unwinding
- Clean removal for long period
- Free from silicone
- Easy to tear off in both length and width
- Can be applied to plastic parts, spoilers, bumper strips, mirrors, but also sheet metal

PHYSICAL PROPERTIES

Code	Description	Width x length	Colour	Pieces per box	Pieces per pallet
CTZ50	Duct tape black	50mm x 50m	Black	18	720
CTG50	Duct tape silver	50mm x 50m	Silver	18	720

NOMINAL VALUES

	VALUE		
Carrier material	Laminated linen		
Width	50mm		
Length	50m		
Thickness	0.30mm		
Mesh	70 mesh		
Tensile strength	44 N/cm		
Stretch	9%		
Adhesive strength on steel N/25mm	18		
Temperature resistance	60°C		
Packing	Per roll in a plastic bag		
Packing unit	18 rolls in a box		